



**SPECIAL PROVISIONS INSERT**

**104.14 — CONES FOR MAINTENANCE OF TRAFFIC**

**CATEGORY 100  
PRELIMINARY**

**SECTION 104 — MAINTENANCE OF TRAFFIC**

**104.14 CONES FOR MAINTENANCE OF TRAFFIC.**

**104.14.02 MATERIALS.**

171 **DELETE:** First paragraph this page “Cones shall be...an upright position”.

**INSERT:** The following.

All cones shall meet MdMUTCD and be new or like new condition. Cones shall be at least 28 in. high, 10 in. diameter at the inside of the base, and reflectorized with 6 in. and 4 in. white retroreflective striping.

**Tall-Weighted Cones.** When specified, tall-weighted cones shall be at least 42 in. high and 7-1/2 in. diameter at the inside of the base. Tall-weighted cones shall be manufactured of low density polyethylene (LDPE) and have high performance wide angle white and orange retroreflective stripes. The stripes shall be horizontal, circumferential and 6 in. wide. Alternate stripe colors with the top stripe being orange. Any nonretroreflective spaces between the orange and white stripes shall not exceed 1/2 in.

**104.14.03 CONSTRUCTION.**

**ADD:** The following after the first paragraph “The Contractor’s name...away from traffic”.

Anchor collars shall be manufactured from recycled rubber. Equip all cones with approved weights or anchor collars\_(15 lb maximum) as needed to maintain an upright position. For tall-weighted cones use anchor collars weighing 10 to 30 lb.